

KSHT-101

Fiber Optic Splice Closure



Features:

- May be used for all fiber optic cable
- Sheath retention & central strength member termination system included
- Ribbed closure construction and lightweight plastic provided strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware is included
- Protection class IP67
- RoHS compliance

Application:

Underground, Aerial, Vault, Wall mounting

Specifications:

Model No	Size (mm) L x W x H	Spliced fiber storage capacity	Cable ports	Max.diameter of cable (mm)	Splice trays
KSHT-101	280 x 200 x 90	48 splices (4x 12 splices) 96 splices (4x 24 splices) ¹	2 ports	Each port for 1 cable with max 14 mm or 2 cables with max 12 mm	Max. 4 trays (Each tray for 12 or 24 splices)

Note: 1) Installing double layers of splices to one groove for each Splice tray T037A

Optional Accessories:

Wall mounting kit, Hanging hook, Air valve, Grounding device

Ordering code:

KSHT-101

-

X

-

X

-

(X)

Numbers of Trays
1x12 ÷ 4x12
1x24 ÷ 4x24

Numbers of Fibers
1 ÷ 48
1 ÷ 96

Optional Accessories
WM Wall mounting kit
HH Hanging hook
AV Air valve
GD Grounding kit

Accessories:



Splice tray 037A



Wall mounting kit

