

KSHT-F02

FTTH Compact Optic Closure

Description:

KSHT-F02 is fiber optic splice closure equipment for multiple uses, which can contact and branch cables. It has 2 inlet port. Device can apply for wall mounting environments. The goods can use in different area and come with perfect sealing, easy installation and indeed our cover made of super strength material and temperature proof. This is our mission to dedicated perfect communication equipment and to ensure every customer has best quality of goods.



Features:

- In-Line closure set
- Wall mounting kit
- Central strength member termination system included
- Construction-lightweight plastic offers strength
- Resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware are included
- ROHS compliance

Application:

Duct installation, Aerial installation, Wall mounting

Basic technical information:

Sealing type	Mechanical
Weight (w/o packing box, kg)	0.17
Working temperature	-40 to +65°C



Specifications:

Model No	Size (mm) L x W x H	Cable ports	Max.capacity	Material
KSHT-F02	179 x 72 x 26	2 ports, each port for cable with max. diameter 6 mm	4 splices	MPP

Ordering code: KSHT-F02



EN ISO 9001:2015
EN ISO 14001:2015
Certified Company
COS 051672 (AQAP 2110) Certified



Member of CENELEC European Committee for
Electrotechnical Standardization



Accredited Calibration Laboratory No. 2315
In Czech Republic & Malaysia
Accredited Testing Laboratory No. 1755



OPTOKON NATO
Supplier Code: 1583G



National Security Authority
Certified: CONFIDENTIAL

ACT_5-08_EN
15/01/2026



DSIA

Member of Defence and Security Industry Association



Member of Czech Chamber of Commerce