

TMVJ

Rack mount cabinet with slide-out shelf

Description:

The **TMVJ** Fixed Cabinet introduces a compact, low cost solution for fiber optic cable termination. The **TMVJ** series is ideal for rack-mounting in confined areas such as equipment enclosures where rack space is limited. The cabinet is equipped with slide-out shelf with splice tray holder. This allows easy access to the splicing area for optical network reconfiguration during operation and prevents damage to fibers prior to routing into adapters. The modular system allows splicing and termination up to 96 fibers in rack height 1U.



*TMVJ-1-48-DSC A-C4
Base unit with patch panel for 24x DSC adapters*

Features:

- FTTH use - holder for minicables or microtubes
- Designed for cable or microtubes termination
- Compact robust design
- Slide-out shelf provides unrestricted access
- Changeable front panel, various adapters
- Coupling adapters mounted on the face panel
- Accommodates up to 96 fibers in 1 rack unit
- Durable powder coat finish
- Cable strain-relief and grounding provisions
- Accepts the industry's most common connector types
- Durable powder coat finish light grey colour (RAL 7038), optionally black colour (RAL 9005)
- Material-Aluminium alloy - low weight and shipment costs

Technical specifications:

PART NUMBER	FIBER CAPACITY		RACK UNITS	DIMENSIONS (HxWxD) mm	SHIP WGT (kg)
	FT-12-XX	FT-24-XX			
TMVJ – 1	12 (24) ¹	24 (48, 96) ¹	1	44 x 432 x 221	1.4

Note: 1) Fiber capacity is valid for SFF connector types, double capacity for duplex adapters (DLC, DSC, QLC)

Coupling panels FT series available for the common used connector adapter types in following configuration:

FT-12-XX 12 pcs ST, FC, SC, DSC, DLC, QLC, E2000, ... adapters
FT-24-XX 24 pcs ST, FC, SC, DSC, DLC, QLC, E2000, ... adapters

Applications:

- Rack-mount
- FTTH networks
- Customer premise remote cable drop




TMVJ-1B-24-DLC S-C-2 front view (RAL 9005)

Product information and specifications:



TMVJ-1-24-DLCF S-C-2/PGR RAL 7038
Internal layout – DLC/PC patch panel and 2 splice cassettes



Empty **FT-24-DSC** front panel

Standard front panels:

FT-12-DSC	12x duplex SC adaptors
FT-24-DSC	24x duplex SC adaptors
FT-12-SC	12x single SC adaptors
FT-24-SC line	24x single SC adaptors in-line
FT-24-SC zigzag	24x single SC adaptors zigzag
FT-12-ST(FC)	12x single ST (FC) adaptors
FT-24-ST(FC)	24x single ST (FC) adaptors
FT-24-DE2	24x duplex E2000 adaptors

Ordering code:

TMVJ-X(B¹) - XX - XX(F²) X(X) - CX /(xPGy³) /(G⁴)

Version - X	
Rack Unit	
1	1U

Fiber Capacity
1 ÷ 96 fibers

Adapter Type - XX	
ST	ST
SC(F)	SC
FC	FC
E2(F)	LSH (E2000)
DE2(F)	Duplex LSH
DSC(F)	Duplex SC
DLC(F)	Duplex LC
QLC(F)	Quadruplex LC

Application - X	
M	Multimode
	OM1,2 (Beige)
S	Singlemode
A	APC

Colours of MM - XX	
TQ	OM3 (Turquoise)
VT	OM4 (Violet)
LG	OM5 (Lime Green)

Splice Trays - X
0 ÷ 4



Plastic cable gland PG 13.5



Grounding accessories

Note:

- B** - Black colour (RAL9005)
- F** - Fixed adaptors by screws
- PG** - Option for cable glands PG 13.5:
x - Number of holes for PG (standard=2)
y - **R** (Right) or **L** (Left) => only one PG
on R or L side from the front view
- G** - Grounding option – Protection
grounding wires installed with grounding



TMVJ-1 with 4 holes (4PG) - back view
(RAL 7038)