

MCPE-04F

End User Terminating Box (Wall Outlet)





Features

- Ergonomically & compact design
- Ability to allow cables to enter from rear or bottom of the unit
- Removable cover for easy access
- Indoor use for wall mount unit used for small and large business premises
- Easily re-enter with a minimum of tools, saves time and cost
- Up to 4 cores (heat shrink protective sleeve) or 2 cores (3M mechanical splices)
- Can hold 4 SC simplex or LC duplex, no ear adaptor
- Can be used for Blown Tube cable or common cables
- Three (3) cable ports, each port for one cable with maximum diameter Ø 10 mm
- RoHS compliance

Specification

Model No.	MCPE-04F
Cable port	3 Cable ports, each port for 1 cable with max Ø 10 mm
Can be used for uncut cable (loop cable)	Yes
Spliced fiber storage capacity	4 Cores (heat shrink protective sleeve) or 2 cores (3M mechanical splices)
Adaptor capacity	4x SC simplex, LC duplex, no ear adaptor
Dimensions	108 x 86 x 27 mm



Ordering Code

NC

No Connectors

MCPE-04F XXX X X **Coupling type Number of adapters** SC SC Multimode М 0 - 4**DLC Duplex LC** S Singlemode

A

CMS 04-18 EN

APC