

KSDT-209A

Fiber Optic Splice Closure (Heat shrink sealing)



Features:

- May be used for cut, uncut and taut sheath applications
- May be used for all fiber optic cable
- Sheath retention & central strength member termination system included
- Ribbed closure construction-lightweight plastic offers strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools, Heat shrink sealing way, All hardware are captive
- Protection class: IP68, ROHS compliance

Application:

Underground, Aerial, Vault, Pole Mounting and Wall Mounting

Specifications:

Model No	Splice Capacity of Tray	Spliced fiber storage capacity	Size (mm) Height x diameter	Cable ports	Max.diameter of cable (mm)
KSDT-209A	12 splices	48 splices (4x12 splices)	300 mm x 178 mm	1 oval port + 3 round ports	1 oval port for 1 cable with max 18 mm 3 round ports , each port for 1 cable with max 15 mm

Ordering code:

KSDT-209A	-	X	-	X
		Numbers of Trays 1x12 ÷ 4x12		Numbers of Fibers 1 - 48

1. *Basic Components:* base, splice trays, velcro strap, dome, O-ring, plastic clamp

2. *Accessories:* Transportation tubes, grounding wire, nylon tie, labeling paper, desiccant, cleaning, tissues aluminum tape, heat shrinkable sleeves

Optional accessories:

BZ03 - Pole mounting kit



BZ04 - Pole mounting kit



- Air valve, Grounding device, Wall mounting kit