

OMK-SR-OTS.2 Diagnostic Set

Code NATO: 1583G KČM: 0062375453050

Description:

Diagnostic set includes measuring instruments and tools for diagnosing faults on fiber optic cables with HMA connectors.

The OPTOKON Diagnostic Set includes two instruments - Light source and Power meter. Both instruments are housed in a hard carry case that meets the requirement of fiber optic networks installation and maintenance teams, who require rugged and lightweight fiber optic test equipment that combines high performance with ease of use and reliable operation.

The Diagnostic Set allows traceable measurements on dual wavelength and data storage to the PC. It includes the hybrid master HMA-FC patchcord for testing of military tactical networks and is comprised of these measurement instruments:

LS-800 light sourcePM-800 power meter

NSN: 6650-16-006-2316 KČM: 0209009700021





Case Peli 1450

Material:

Case: Copolymer Polypropylene Structural Resin

Latches: ABS

O' Ring: Neoprene sponge Pins: Stainless Steel

Purge Valve: ABS with Gore-Tex membrane

Foam: Polyester

Standard:

MIL STANDARD MIL-C-4150J

IP67 in accordance with EN60529/91 & IEC60529/68

Air Transportation Association Spec. 300



Measuring equipment:

LS-800

- Small size, light weight
- Modulation CW, 270 Hz, 1 kHz, 2 kHz
- AWD function (Auto Wavelength Detection)
- Changeable output connectors
- Battery status indicator
- User manual
- Up to 7 light source combinations
- Powered by 3 AA type batteries, battery charging via USB port



PM-800

- Small size, light weight
- Up to 6 working wavelength
- Absolute and Relative optical power measurement
- Detection of modulation 270 Hz, 1 kHz, 2 kHz
- AWD (Auto Wavelength Detection) function
- Two levels high capacity memory
- SmartProtocol PC software
 - memory download
 - reporting solution
- **USB**
- Powered by 3 AA type batteries, battery charging via USB port
- Auto Off function
- Battery status indicator
- Easy to use with menu navigation
- Universal 2,5 mm testing adaptor



Application:

- measurement of insertion loss
- measurement of absolute and relative values
- measurement of two wavelength
- measurement of optical networks during construction and operation

Equipment included in OMK-SR-OTS.2:

Description	Qty	Note
Hard carry case	1	Peli 1450, IP67
Measuring instruments:	1	Light source: LS-800V-P2-FC-850-30
	1	Power meter: PM-800V
Reference patch cords: FC	1	PC-28OM2-J-002
HMA/FC	2	HMA-J-4xPC-LD4OM2-J-002
HMA-HMA	1	HMA-J/LD4 OM2-J-002
Measuring adapter	1	A-FC/PC-02-240-12
USB cable	1	Data transfer to PC, charging
CLETOP-A	1	Connector cleaner
Cleaning wipes	1	Cleaning connectors
External power supply	1	Charging internal battery
User manuals	2	Light source, Power meter
Quick start manual	1	Check of the route, Measuring the output of the converter LMC