


Universal CST Armoured Multitube Cable 12-288F (NC)

Fibre optic cable with full protection against rodents for direct burial installation



Picture not to scale. For illustration only.

Fibre Type	G.652.D, G.657.A1, G.657.A2, G.655, OM2, OM3, OM4
Fibre colour	EIA/TIA-598A
Tube colour	EIA/TIA-598A
Tube	Gel-Filled PBT buffer tube
Tube filling compound	Low-viscosity filling gel
Central strength member	FRP rod (coated if necessary)
Peripheral strength members	Water-swellable glass yarns
Core wrapping	Water-swellable tape
Armouring	Corrugated steel tape , longitudinally under outer jacket
Outer jacket material	UV resistant halogen-free flame-retardant thermoplastic compound

Number of fibres	12	24	48	60	72	96	144	288	
Number of fibres in tube	12	12	12	12	12	12	12	12	
Tube count (layers)	1	2	4	5	6	8	12	24(9+15)	
Filler count	5	4	2	1	0	0	0	0	
Nominal outer diameter (mm)	10.4	10.4	10.4	10.4	10.4	11.4	13.7	15.8	
Outer jacket thickness (mm)				1.5					
Calc. cable weight (kg/km)	137	137	138	138	139	164	215	271	
Short-term tensile strength (N)	2800	2800	2800	2800	2800	5500	5800	4600	IEC 60794-1-101
Long-term tensile strength (N)	900	900	900	900	900	1800	1900	1450	IEC 60794-1-101
Short-term crush resistance (N/100 mm)				3500					IEC 60794-1-103
Long-term crush resistance (N/100 mm)				1050					IEC 60794-1-103
Max. impact loading (Nm)				25					IEC 60794-1-104
Min. bend radius not load (OD)				15					IEC 60794-1-111
Min. bend radius load (OD)				20					IEC 60794-1-111
Operating temperature range (°C)				-40 to +70					IEC 60794-1-201
Storage temperature range (°C)				-40 to +70					IEC 60794-1-201
Installation temperature range (°C)				-15 to +50					IEC 60794-1-201
Water tightness (1 m / 24 hrs.)				No leakage					IEC 60794-1-205
Class of fire reaction				Fca					EN 50575, EN 13501-6

Number of Fibers	Cable Code (Ordering Code)	Delivery length	Packing
12	OPK-U-MTFDS-12(6x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
24	OPK-U-MTFDS-24(6x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
48	OPK-U-MTFDS-48(6x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
60	OPK-U-MTFDS-60(6x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
72	OPK-U-MTFDS-72(6x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
96	OPK-U-MTFDS-96(8x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
144	OPK-U-MTFDS-144(12x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum
288	OPK-U-MTFDS-288(24x1.7)LTGXH-xx-BK	2100 m ± 5%	Solid wooden non-returnable drum

xx – fibre type (see Cable code datasheet)

Print legend: Manufacturer - Cable type – lot number- length marking per 1 m (customer print legend available on request)

Note: Cable marking using the Hot-foil method is done in white. If overprinting is necessary, the color of the text is yellow.